



## Marine Cylinder Lubricant Concentrate

### Applications

TALUMAR B may be used to manufacture Marine cylinder lubricants for slow speed two-stroke engines. It is a component of the Talusia range of marine cylinder lubricants.

### Features and Benefits

Specially formulated to provide excellent neutralizing capacity to the lubricant and excellent deposit control.

### Description

TALUMAR B is a concentrate designed to manufacture cylinder lubricant for slow speed two-stroke engines.

TALUMAR B is a component of the Talusia range of marine cylinder lubricants approved by OEMs MAN D&T and WinGD.

### Typical Characteristics

|                            | Methods     | Units    |      |
|----------------------------|-------------|----------|------|
| Specific Gravity at 15.6°C | ASTM D 4052 |          | 1110 |
| Viscosity at 100°C         | ASTM D 445  | cSt      | 205  |
| Flash Point (COC)          | ASTM D 93   | °C       | 151  |
| Pour Point                 | ASTM D 97   | °C       | -15  |
| BN                         | ASTM D 2896 | mg KOH/g | 301  |

Characteristics of this chart are indicative typical values.

### Handling, Health & Safety

TALUMAR B is an additive. All additives, of any kind, should always be handled with great care, particularly avoiding any contact with the skin or eyes. Prevent any risk of splashing, and keep away from combustible materials. Store under cover and away from any risk of contamination.

A safety data sheet complying with current legislation is available at: [www.quickfds.com](http://www.quickfds.com) and [www.totallubmarine.com](http://www.totallubmarine.com)